



**Sun-In-One™**  
New Electrical Solar Light and Power Products



## SPECIFICATIONS

AVERAGE WATTAGE	20 Watts, 1-20W LED
APPROXIMATE EQUIVALENCE	150 Metal Halide Lamp
INPUT VOLTAGE	12-24 VDC
COLOR TEMP (ANSI)	Cool White (6500K) Warm White (3200K)
CRI (Color Rendering Index)	80
OUTPUT (LUMENS)	2000 (WW), 2100 (CW)
BEAM ANGLE	50-70 Degrees
DIMENSIONS	11.2" (L) X 10.1" (W) X 8" (D)
LIFE SPAN	>50,000 Hours
OPERATING TEMPERATURE	-40°F - 140°F
ENVIRONMENTAL RATING	IP65
WARRANTY	5 Years
CERTIFICATIONS	CE, RoHS

## LED Flood Light - 20W



### ORDERING INFORMATION FOR 80W LED FLOOD LIGHT

**GL-FLS-80W-WW (3200K)**  
**GL-FLS-80W-CW (5000K)**

### FEATURES / BENEFITS

- High Luminance and Low Power Consumption
- Super Long Life and Simple Installation
- Replaces for 150W Metal Halide
- Longer life than Metal Halide Lamp
- 70% Energy Savings compared to MH
- No Destructive UV or RF Interference
- No Mercury, and is RoHS Compliant



**Sun-In-One™**  
suninone.com  
302-762-3100

