



**Sun-In-One™**  
New Electrical Solar Light and Power Products



## SPECIFICATIONS

AVERAGE WATTAGE	80 Watts, 1-70W LED	
APPROXIMATE EQUIVALENCE	320 Metal Halide Lamp	
INPUT VOLTAGE	85-265 VAC	
COLOR TEMP (ANSI)	Cool White (6500K)	
	Warm White (3200K)	
CRI (Color Rendering Index)	Ra>75	
OUTPUT	9600 Lumens	
VIEW ANGLE	105 Degrees	
DIMENSIONS	15.6" (L) X 11.2" (W) X 4.7" (D)	
LIFE SPAN	>50,000 Hours	
OPERATING TEMPERATURE	-13°F - 140°F	
RATINGS	IP65	
WARRANTY	5 Years	
CERTIFICATIONS	ETL and RoHS	
TOTAL HARMONIC DISTORTION	<9%	
POWER FACTOR	>95%	
POWER EFFICIENCY	>85%	
FREQUENCY RANGE	47-63Hz	
Eave/Emax ILLUMINESSENCE	(Height) 6M	30/69 Lux
	(Height) 8M	13/40 Lux
	(Height) 10M	8/22 Lux

## LED Flood Light - 80W



### FEATURES / BENEFITS

- High Luminance and Low Power Consumption
- Super Long Life and Simple Installation
- Replaces for 320W Metal Halide
- Longer life than Metal Halide Lamp
- 70% Energy Savings compared to MH
- No Destructive UV or RF Interference
- No Mercury, and is RoHS Compliant

### ORDERING INFORMATION FOR 80W LED FLOOD LIGHT

**GL-FLS-80W-WW (3200K)**  
**GL-FLS-80W-CW (5000K)**



**Sun-In-One™**  
suninone.com  
302-762-3100

