



**Sun-In-One™**  
New Electrical Solar Light and Power Products




## SPECIFICATIONS

AVERAGE WATTAGE	10 Watts per Tube
LUMINOUS EFFICACY	150 lm /W (4000K) 155 lm /W (5000K)
INPUT VOLTAGE	95-305 VAC
COLOR TEMP (ANSI)	4000K (WW) or 5000K (CW)
CRI (COLOR RENDERING INDEX)	>85 95 Available
R9	>13
LUMEN OUTPUT	1550 Lumens (CW)
BEAM ANGLE	210 Degrees
DIMENSIONS	599 mm X 28 mm
LIFE SPAN	>100,000 Hours
OPERATING TEMPERATURE	-10° F - 130° F (-40° C - 60° C)
RATINGS	Indoor Applications
WARRANTY	7 Years, Non-prorated
CERTIFICATIONS	ETL, UL 1993, UL 1598C, DLC
DRIVER	Custom UL Class 2
POWER FACTOR	>90%(277 VAC) : >99% (120 VAC)
TOTAL HARMONIC DISTORTION	<15% (277 VAC) : <10% (120 VAC)
OFF-STATE POWER	0 Watts

## LED T8 Tube Light 2ft - 210° - 10W

Built on our DesignLights™ Consortium® Certified Platform

*Achieves the highest electrical and optical quality standards established in the industry*



## FEATURES / BENEFITS

- 70% Energy Savings over Fluorescent
- High Luminance and Low Power Consumption
- 7 year / 100,000 Hour Warranty
- 10x Longer Life than Fluorescent Tube
- 210 Degree Illumination Angle
- No UV, No RF Interference
- No Mercury, RoHS Compliant
- Significantly Reduced Maintenance Costs

## ORDERING INFORMATION FOR LED T8 TUBE LIGHT 2 FT - 210° - 10W

**SPECIFY LENS AS C (CLEAR) OR F (FROSTED)**

**SIO-T82F-HBF-WW-10W-GLCP (4000K)**  
**SIO-T82F-HBF-CW-10W-GLCP (5000K)**



**Sun-In-One™**  
suninone.com  
302-762-3100

