



Sun-In-One™
New Electrical Solar Light and Power Products



SPECIFICATIONS

AVERAGE WATTAGE	30 Watts per Tube
LUMINOUS EFFICACY	150 lm/W (4000K) 155 lm/W (5000K)
INPUT VOLTAGE	95-305 VAC
COLOR TEMP (ANSI)	4000K (WW), 5000K (CSW)
CRI (Color Rendering Index)	>85 95 Available
R9	>13
LUMEN OUTPUT	4650 Lumens (CW)
BEAM ANGLE	210 Degrees
DIMENSIONS	1797 mm x 28 mm
LIFE SPAN	>100,000 Hours
OPERATING TEMPERATURE	-10°F - 130°F (-40°C - 60°C)
RATINGS	Indoor Applications
WARRANTY	7 Years, Non-prorated
CERTIFICATIONS	ETL, UL 1993, UL 1598C
DRIVER	Custom UL Class 2
POWER FACTOR	>90% (277 VAC) : >99% (120VAC)
TOTAL HARMONIC DISTORTION	< 15% (277 VAC) : <10% (120VAC)
POWER OFF-STATE	0 Watts

ORDERING INFORMATION FOR
LED T8 TUBE
6 FT - 210° - 30W
SIO-T86F-30W-GLCP



LED T8 Tube Light 6ft - 210° - 30W

Built on our DesignLights™
Consortium® Certified Platform

*Achieves the highest electrical and optical
quality standards established in the industry*




1
DRIVER

X

LAMP

LAMP



FEATURES / BENEFITS

- 70% Energy Savings over Fluorescent
- High Luminance and Low Power Consumption
- 7 year / 100,000 Hour Warranty
- 10x Longer Life than Fluorescent Tube
- 210 Degree Illumination Angle
- No UV, No RF Interference
- No Mercury, RoHS Compliant
- Significantly Reduced Maintenance Costs



Sun-In-One™
suninone.com
302-762-3100

