



**Sun-In-One™**  
New Electrical Solar Light and Power Products



## SPECIFICATIONS

AVERAGE WATTAGE	34 Watts per Tube
LUMINOUS EFFICACY	150 lm/W (4000K) 155 lm/W (5000K)
INPUT VOLTAGE	95-305 VAC
COLOR TEMP (ANSI)	4000K (WW) or 5000K (CW)
CRI (COLOR RENDERING INDEX)	> 85 95 available
R9	> 13
LUMEN OUTPUT	5270 Lumens (CW)
ILLUMINATION SPREAD	210 Degrees
LED TUBE DIMENSIONS	2396 mm X 28 mm
LIFE SPAN	>100,000 Hours
OPERATING TEMPERATURE	-10° F - 130° F (-40° C - 60° C)
RATINGS	Indoor Applications
WARRANTY	7 Years, Non-prorated
CERTIFICATIONS	ETL, UL 1993, UL 1598C
DRIVER	Custom UL Class 2
POWER FACTOR	> 90%(277 VAC) : > 99% (120 VAC)
TOTAL HARMONIC DISTORTION	< 15% (277 VAC) : < 10% (120 VAC)
OFF-STATE POWER	0 Watts

## ORDERING INFORMATION FOR LED T8 TUBE LIGHT 8 FT - 210° - 34W

**SPECIFY LENS AS C (CLEAR) OR F (FROSTED)**


**SIO-T88F-WW-30W (4000K)**  
**SIO-T88F-CW-30W (5000K)**



## LED T8 Tube Light 8ft - 210° - 34W

Built on our DesignLights™  
Consortium® Certified Platform

*Achieves the highest electrical and optical  
quality standards established in the industry*



## FEATURES / BENEFITS

- 70% Energy Savings over Fluorescent
- High Luminance and Low Power Consumption
- 7 year / 100,000 Hour Warranty
- 10x Longer Life than Fluorescent Tube
- 210 Degree Illumination Angle
- No UV, No RF Interference
- No Mercury, RoHS Compliant
- Significantly Reduced Maintenance Costs



**Sun-In-One™**  
suninone.com  
302-762-3100

