



Sun-In-One™
New Electrical Solar Light and Power Products




SPECIFICATIONS

| | |
|-----------------------------|-------------------------------------|
| AVERAGE WATTAGE | 60 Watts per Tube |
| LUMINOUS EFFICACY | 150 lm/W (4000K) 155lm/W (5000K) |
| INPUT VOLTAGE | 95-305 VAC |
| COLOR TEMP (ANSI) | 4000K (WW) or 5000K (CW) |
| CRI (COLOR RENDERING INDEX) | > 85 95 available |
| R9 | >13 |
| LUMEN OUTPUT | 9300 Lumens (CW) |
| ILLUMINATION SPREAD | 210 Degrees |
| LED TUBE DIMENSIONS | 2396 mm X 28 mm |
| LIFE SPAN | >100,000 Hours |
| OPERATING TEMPERATURE | -10° F - 130° F (-40° C - 60° C) |
| RATINGS | Indoor Applications |
| WARRANTY | 7 Years, Non-prorated |
| CERTIFICATIONS | ETL, UL 1993, UL 1598C |
| DRIVER | Custom UL Class 2 |
| POWER FACTOR | >90%(277 VAC) : >99% (120 VAC) |
| TOTAL HARMONIC DISTORTION | <15% (277 VAC) : <10% (120 VAC) |
| OFF-STATE POWER | 0 Watts |

LED T8 Tube Light 8ft - 210° - 60W

Built on our DesignLights™ Consortium® Certified Platform

Achieves the highest electrical and optical quality standards established in the industry



FEATURES / BENEFITS

- 70% Energy Savings over Fluorescent
- High Luminance and Low Power Consumption
- 7 year / 100,000 Hour Warranty
- 10x Longer Life than Fluorescent Tube
- 210 Degree Illumination Angle
- No UV, No RF Interference
- No Mercury, RoHS Compliant
- Significantly Reduced Maintenance Costs

ORDERING INFORMATION FOR LED T8 TUBE LIGHT 8 FT - 210° - 60W

SPECIFY LENS AS C (CLEAR) OR F (FROSTED)

SIO-T88F-WW-60W (4000K)
SIO-T88F-CW-60W (5000K)



Sun-In-One™
suninone.com
302-762-3100

