



Sun-In-One™
New Electrical Solar Light and Power Products



SPECIFICATIONS

| | |
|--------------------------|--------------------------------|
| POWER | 150 Watt |
| COLOR TEMPERATURE (CCT) | 4000K, 5000K, 5700K |
| LED EFFICIENCY | >135 Lm/W |
| LAMP EFFICIENCY | >95 Lm/W, >110 Lm/W |
| LUMINOUS FLUX | 15,000 Lm |
| INPUT VOLTAGE/FREQUENCY | AC 100~277V 50/60Hz |
| PHOTO CELL | Optional |
| POWER FACTOR | >0.95 |
| PSU | Class II & 0-10V Dim |
| CONTROL SYSTEM | Intelligent System Option |
| LIGHT BEAM ANGLE | Horiz Axis 150°, Vert Axis 85° |
| LIGHT DISTRIBUTION | Type-II / III |
| COLOR INDEX (CRI) | Ra>75 |
| OPERATING TEMP./HUMIDITY | -40°C – 45°C / 10% ~ 90% RH |
| STORAGE TEMPERATURE | -40°C – 60°C |
| WORKING LIFE | 50,000 Hrs |
| IP RATING | IP66 |
| IK RATING | IK08 |
| NET WEIGHT | 26.5 Lbs (12 Kg) |
| PRODUCT DIMENSIONS | L 32.6" x W 15" x H 6.8" |
| PACKING DIMENSIONS | 39" x 17.7" x 11" 1pcs/Carton |
| CERTIFICATIONS | TUV, CE, ENEC, UL, DLC |
| WARRANTY | 5 Years |

ORDERING INFORMATION FOR LED STREET LIGHT 150 WATTS

SIO-150/4000K

SIO-150/5000K

SIO-150/5700K

INDICATE INTELLIGENT CONTROL SYSTEM OPTION AT TIME OF ORDER

LED Street Light 150 Watts



FEATURES / BENEFITS

- Enhances Security
- LED Diodes provide Super High Luminance and Low Power Consumption
- Super Long Life
- Ultra-white Tempered Glass Allows for Brighter & More Intense Light with Less Glare
- Tool-free Maintenance and Easy Install
- Ultra-light Design and High Quality Materials
- Aluminum Alloy Housing – Less Overall Weight
- Module Shape Permits Rain to Wash Away Accumulated Dust & Dirt
- Optional Photo Cell is Available
- Intelligent Control System Option is Available



Sun-In-One™
suninone.com
302-762-3100

