

#### **SPECIFICATIONS**

POWER	35 Watt
COLOR TEMPERATURE (CCT)	4000K, 5000K, 5700K
LED EFFICIENCY	>135 Lm/W
LAMP EFFICIENCY	>95 Lm/W, >110 Lm/W
LUMINOUS FLUX	3,800 Lm
INPUT VOLTAGE/FREQUENCY	AC 100~277V 50/60Hz
PHOTO CELL	Optional
POWER FACTOR	>0.95
PSU	Class II & 0-10V Dim
CONTROL SYSTEM	Intelligent System Option
LIGHT BEAM ANGLE	Horiz Axis 150°, Vert Axis 85°
LIGHT DISTRIBUTION	Type-II / III
COLOR INDEX (CRI)	Ra>75
OPERATING TEMP./HUMIDITY	-40°C – 45°C / 10% ~ 90% RH
STORAGE TEMPERATURE	-40°C – 60°C
WORKING LIFE	50,000 Hrs
IP RATING	IP66
IK RATING	IK08
NET WEIGHT	10.1 Lbs (4.6 Kg)
PRODUCT DIMENSIONS	L 27.2" x W 12" x H 5.3"
PACKING DIMENSIONS	29" x 13.8" x 7.5" 1pcs/Carton
CERTIFICATIONS	TUV, CE, ENEC, UL, DLC
WARRANTY	5 Years

### ORDERING INFORMATION FOR LED STREET LIGHT 35 WATTS

SIO-35/4000K SIO-35/5000K SIO-35/5700K

INDICATE INTELLIGENT CONTROL SYSTEM OPTION AT TIME OF ORDER

# LED Street Light 35 Watts



## FEATURES / BENEFITS

- Enhances Security
- LED Diodes provide Super High Luminance and Low Power Consumption
- Super Long Life
- Ultra-white Tempered Glass Allows for Brighter & More Intense Light with Less Glare
- Tool-free Maintenance and Easy Install
- Ultra-light Design and High Quality Materials
- Aluminum Alloy Housing Less Overall Weight
- Module Shape Permits Rain to Wash Away Accumulated Dust & Dirt
- Optional Photo Cell is Available
- Intelligent Control System Option is Available



副調
E PRA

Products are warranted only to meet Sun-In-One™ data sheet specifications. Products and specifications are subject to change without notice.